



"Includes AsureID Solo™ card printing software – ideal for entry level, single sided card design and production"

# PR 5300

The PR5300 Printer offers brilliant images printed on CR80 and CR79 PVC cards with thicknesses ranging from 20 to 50 mils. Offering Nisca's high quality design capabilities, the PR5300 series provides a very well priced full-featured printer.

Originally introduced in 2000, the PR5300 has proven its performance and reliability over the years in applications such as driving licenses, printing bureaus, access control badges, and standard corporate identification cards.

The series offers many add-on modules that include magnetic stripe as well as in-line over-lamination with full 1.0mil patch and thinfilm / foil edge-to-edge materials.

Today the printer sells on its strong reliability, excellent price point, and brilliant image reproduction. And now it features a two-year warranty, so it's a safe investment for your identification card printing needs.



**Features:**


- ♦ Full color edge to edge printing
- ♦ 300dpi dye-sublimation printing technology
- ♦ Industry leading 24-bit continuous tone printing
- ♦ 103 cards per hour printing speed
- ♦ Dual sided printing
- ♦ Dual sided lamination with alternating patch options
- ♦ USB 2.0, Micro SCSI II, or Parallel
- ♦ Full Windows compatibility

**Accessories:**


- ♦ Security over-laminate
- ♦ 1mil patch
- ♦ Thinfilm/foil
- ♦ Encoding
- ♦ Magstripe

**Cleaning Kits:**


- ♦ Fully accessorized 10,000 print kits
- ♦ Variable UV printing
- ♦ ISO9001 & ISO14001 Certifications




Double-Sided




2 Years Warranty



35secs/card YMCKO



1.70mm



300DPI



# Nisca PR 5300

## Technical Details



### Specifications:

Printing system	300dpi, 24-bit continuous tone printing up to 16.7million colors
Printing method	Thermal transfer dye-sublimation
Print media	PVC or polyester cards with polished PVC finish
Media size	CR-80: 3.375" x 2.125" / 85.6 x54mm CR-79: 3.303" x 2.051" / 83.9mm x 52.1mm
Media thickness	.020" (20mil) to .050" (50mil) / .508mm to 1.72mm
Print area	Edge to edge
Input hopper	100 cards
Output hopper	100 cards
Image memory	8MBwith parallel processing, four memory modes
System memory	2.25MB
Display	LCD 16 character 2-line display shows printer status and diagnostic prompts

### Print ribbons options

Print speed*	
YMCO Single Side	104 cards/hr
YMCO/K Dual side	66 cards/hr
YMCKO/K Dual side	60 cards/hr
YMCK/K w/Lam	84 cards/hr
YMCK w/Lam	72 cards/hr
Encoding options	Integrated driver control for all encoding that includes ISO standard Magstrip w/ dual high- and low-coercivity standard
Interface	USB2.0 Mico-SCSI II or Parallel
Dimensions	16.57" (h) x 10.66" (w) x 13.03" (d) / 421 x 271 x 331mm
Weight	26.6lbs. / 13kg
Operating temperature	65 to 80 F / 18 to 27C
Power source	ACPower sourceAC100/240v 50/60Hz auto-switching
Agency listing	UL/CE/FCC
Drivers	Windows® compatible
Warranty	2-year return to depot service printer warranty, 1-year unlimited prints print head warranty
Options	PR 5302 Laminator PR 5301 Magstripe encoder

\* Print speed indicates approximate multiple job print speed and is measured from the time a card feeds into the printer to the time it ejects from the printer. Print speeds do not include encoding time or the time needed for the PC to process the image. Process time is depend on the size of the file, the CPU, the amount of PC memory, the interface (SCSI, USB, Parallel), and the amount of resources at the time of the print job.